





Spectrum® Plasma Cutter Comparison

				
CUTTING CAPABILITY	Spectrum 375 X-TREME™	Spectrum 625 X-TREME™	Spectrum 875	Spectrum 875 Auto-Line™
Rated Sever	3/8 in. 5/8 in.	5/8 in. 7/8 in.	7/8 in. 1-1/4 in.	7/8 in. 1-1/4 in.
POWER				
Rated output (amps/duty cycle)	30 A at 40%	40 A at 60%	60 A at 40% 1-phase (230 V)	60 A at 50% 1-phase (230 V) 60 A at 60% 3-ph. (380–575 V)
Input power V	120/240 1-phase	120/240 1-phase	208/230 1-phase	208–575 1- or 3-phase
Max amperage A	30	40	60	60
WEIGHT with TORCH	19 lb.	21 lb.	49 lb.	54 lb.
FEATURES				
MVP™	■	■		
X-CASE™	■	■		
Fan-On-Demand™	■	■	■	■
Auto-Refire™	■	■	■	■
Wind Tunnel Technology™	■	■	■	■
Automatic air regulation	■	■	■	■
Ultra-Quick Connect™ torch		■	■	■
Automation options			■	■
Auto-Line™				■
PRICING	\$	\$\$	\$\$\$	\$\$\$\$