
MATERIAL: .250 THK CR STEEL ASTM A1008 CS TYPE B FINISH: PAINT POWDER BLACK PER MILLER PAINT STANDARD 179295

NOTE: REMOVE ALL BURRS AND SHARP EDGES

HOLE LEGEND

A - 0.257 DIA. THRU
B - 0.404 DIA. THRU W/C'SINK 82° X 0.633 DIA.
C - 0.246 DIA. THRU W/C'SINK 82° X 0.484 DIA.
D - 1/4-20 UNC-2B THRU
E - 0.281 DIA. THRU



| | | | | | Tolerances Unless Otherwise Specified | |
|-----|----------|------------|--------|--|--|-------|
| | | | | | | |
| Е | 10-10-14 | PEK BAS | 023325 | ADDED (3) 'B' HOLES @ THE 1.181[20] AND 5.906[150] DIMENSIONS | Decimal ±: .015 | Title |
| D | 03-25-13 | PEK DWS | 019473 | ADDED SET OF 'D' HOLES AT THE 4.500[114.30] DIMENSION AND A SET OF 'E' HOLES | Fractional ±: | Title |
| С | 12-21-05 | DWS KS | 326 | MOVE 'D' HOLES 5/16 TO THE RIGHT AND CHANGE FROM .247 TO .201 FOR TAPPING 1/4-20 | | |
| В | 05-10-05 | JD DWS | | INITIAL RELEASE | Angular ±: 1° | |
| 1 | | JD DWS | | PROTOTYPE | Finish: | Drawn |
| Rev | Date | Ву | ECO | Revision Description | | Date: |

| /// Miller | MILLER ELECTRIC MFG. CO., APPLETON, WI. USA | | | | | | | |
|-----------------------------------|--|--------------|-----|--|--|--|--|--|
| Title: BRACKET, MTG MOTOMAN/FANUC | | | | | | | | |
| WIRE DRIVE ROBOT | | | | | | | | |
| | | | | | | | | |
| DRAWING NOT TO SO | CALE | CONFIDENTIAL | | | | | | |
| Drawn By: JD | Size | Drawing No | Rev | | | | | |
| Date: 05-10-05 | С | 224302 | Ε | | | | | |