

# MILLER AUTO BODY WELDING PRODUCT GUIDE

	MATERIAL THICKNESS RANGE	WELD PROCESSES					WIRE TYPES			VOLTAGE INPUT			
		MIG	PULSED MIG	DC TIG	AC TIG	STICK	PLASMA CUTTING	STEEL	ALUMINUM	SILICON-BRONZE	110-120V	208V	220-240V
951601													
<b>MILLERMATIC® 141</b>	24 ga. (0.6 mm) to 3/16 in. (4.8 mm)	✓						✓	✓	✓	✓		
951715													
<b>MILLERMATIC® 211 AUTO PACKAGE</b>	24 ga. (0.6 mm) to 3/8 in. (9.5 mm)	✓						✓	✓	✓	✓		✓
907693													
<b>MULTIMATIC® 215</b>	24 ga. (0.6 mm) to 3/8 in. (9.5 mm)	✓		✓		✓		✓	✓	✓	✓		✓
907757													
<b>MULTIMATIC® 220 AC/DC</b>	24 ga. (0.6 mm) to 3/8 in. (9.5 mm)	✓		✓	✓	✓		✓	✓	✓	✓		✓
907321													
<b>MILLERMATIC® 252</b>	22 ga. (0.8 mm) to 1/2 in. (13 mm)	✓						✓	✓	✓		✓	✓
951821													
<b>MILLERMATIC® 255 AUTO PACKAGE</b>	24 ga. (0.6 mm) to 1/2 in. (13 mm)	✓	✓					✓	✓	✓		✓	✓
907627													
<b>DIVERSION™ 180</b>	24 ga. (0.6 mm) to 3/16 in. (4.8 mm)			✓	✓			✓	✓		✓	✓	✓
907722													
<b>THUNDERBOLT® 210</b>	Up to 1/2 in. (13 mm)					✓		✓					✓
907579													
<b>SPECTRUM® 625 X-TREME™</b>	Up to 5/8 in. (15.9 mm)						✓				✓		✓

▶ **Visit [MillerWelds.com/bluecollision](http://MillerWelds.com/bluecollision)**

to get technical specs on these easy-to-use products and learn more about our complementary accessories.